

HEATLINE OÜ
 info@heatline.ee
 Tallinn, Harju maakond
 +372 53033990



EX-Drum Heater - 230V
EX-Base Heater - 230V



Our **EX-Drum Heaters** and **EX-Base heaters** are used to provide medium flow and process temperature in hazardous environments. The special design including a self-regulating heating cable embedded in a solid metal housing ensures the maximum in safety at operating conditions. Using this design and additional temperature limiter is not necessary.

Protection class: 1
 System of protection: IP 65
 Permissible ambient temp.: -40 - +50°C
 Rated voltage: max. 254 Vac
 Zone: Gas: 1,2, Dust: 21, 22
 Temperature class: T2, T4, T6
 Ingress protection: IP6X (IP65)

Part no.	Std. sizes (ltr)	Height (mm)	Inner dia. (ID) (mm)	Outer dia. (OD) (mm)	Temp. class	Nominal power (W)	Nominal Voltage (Vac)	Weight (kg)
Drum Heaters								
SAN-SRX	200	990	650	770	T1/T2	3930	230	60
SAN-SRQ	200	990	650	770	T3/T4	3990	230	60
SAN-SRB	200	990	650	770	T5/T6	1810	230	60
Base Heaters								
SAN-SRX	200	78	-	546	T1/T2	1150	230	20
SAN-SRQ	200	78	-	546	T3/T4	1170	230	20
SAN-SRB	200	78	-	546	T5/T6	530	230	20
Insulated lid								
SAN-lid	200	85	790	798		-	-	20