

Gutter Safe

Shielded 2-wired 7 mm heating cable 25 W/m with mounted thermostat and Schuko plug for frost protection of gutters and drainpipes. When the Gutter Safe is installed correctly, it will prevent frost damage to installations and buildings caused by ice and snow building up in gutters and drainpipes – as well as injuries caused by fallen icicles.

The thermostat turns the heat on, when the temperature is about 5 °C and off again at about 15 °C.

The heating cable is placed in the length of the gutter and fastened by Hestcom's cable clips. In order to be sure to achieve the desired effect, it is possible to lead the cable forward and back (2 cable lengths). The installation is very simple and allows an easy change if needed. It is the same cable used in the gutter and in the drainpipe.

When the heating cable is installed in the drainpipe, it is retained of spacers and a plastic chain that is hanging from a small metal rod, which is placed at the top of the drainpipe. If desired, the installation can easily be dismantled, when the winter is over.



Schuko plug

Technical Data



Voltage	230 V ~ 50 Hz
Cable diameter	Ø7 mm
Insulation inner sheath	Teflon, FEP
Authorisation	CE
Cable buildup	2 conductors + ground shield
Ground shield	Tinned copper
Outer sheath	PVC
Max. temp. on cable	90°C
Warranty	3 years
Resistance tolerance	-5 % /+10 %

Gutter Safe

Item	Type	Description	Power	Current	Length	Resistance
51760013	HC64E25T-0013-S	Gutter Safe 1.3 m, Schuko plug	30 W	0.13 A	1.3 m	1672.8 Ω
51760025	HC64E25T-0025-S	Gutter Safe 2.5 m, Schuko plug	62 W	0.27 A	2.5 m	836.4 Ω
51760038	HC64E25T-0038-S	Gutter Safe 3.8 m, Schuko plug	100 W	0.43 A	3.8 m	557.6 Ω
51760051	HC64E25T-0051-S	Gutter Safe 5.1 m, Schuko plug	130 W	0.57 A	5.1 m	418.2 Ω
51760063	HC64E25T-0063-S	Gutter Safe 6.3 m, Schuko plug	160 W	0.70 A	6.3 m	334.6 Ω
51760076	HC64E25T-0076-S	Gutter Safe 7.6 m, Schuko plug	190 W	0.83 A	7.6 m	278.8 Ω
51760089	HC64E25T-0089-S	Gutter Safe 8.9 m, Schuko plug	220 W	0.96 A	8.9 m	239.0 Ω
51760101	HC64E25T-0101-S	Gutter Safe 10.1 m, Schuko plug	250 W	1.09 A	10.1 m	209.1 Ω
51760114	HC64E25T-0114-S	Gutter Safe 11.4 m, Schuko plug	290 W	1.26 A	11.4 m	185.9 Ω
51760126	HC64E25T-0126-S	Gutter Safe 12.6 m, Schuko plug	320 W	1.39 A	12.6 m	167.3 Ω
51760152	HC64E25T-0152-S	Gutter Safe 15.2 m, Schuko plug	380 W	1.65 A	15.2 m	139.4 Ω
51760190	HC64E25T-0190-S	Gutter Safe 19.0 m, Schuko plug	480 W	2.09 A	19.0 m	111.5 Ω
51760266	HC64E25T-0266-S	Gutter Safe 26.6 m, Schuko plug	670 W	2.91 A	26.6 m	79.7 Ω
51760379	HC64E25T-0379-S	Gutter Safe 37.9 m, Schuko plug	950 W	4.13 A	37.9 m	55.8 Ω
51760506	HC64E25T-0506-S	Gutter Safe 50.6 m, Schuko plug	1270 W	5.52 A	50.6 m	41.8 Ω
51760664	HC64E25T-0664-S	Gutter Safe 66.4 m, Schuko plug	1660 W	7.22 A	66.4 m	31.9 Ω
51760854	HC64E25T-0854-S	Gutter Safe 85.4 m, Schuko plug	2140 W	9.30 A	85.4 m	24.8 Ω