



## MOBILE WINTER MAT

### Defrosting of outdoor areas

The mobile winter mat is made of a durable and fire-retardant PVC canvas, which is sealed and suitable for outdoor use.

The winter mat consists of a layer of reflective aluminum foil and insulation at the top, a heating mat at the bottom, which is equipped with a robust heating cable that spreads heat evenly over the entire surface. The winter mat is equipped with suspension straps for easy storage and transport, as well as metal eyelets for suspension on each of its long sides.

The mobile heating mat has many areas of applications within thawing, for example before digging (20 - 50 cm per day) and thawing of local frost, for example in front of doors and entrances. Another application is heating, for example, moulds, sand, cable drums, machines etc.

The heating mat is optionally available with a 3-pole IEC 309 plug, DK plug or Schuko plug.

The winter mat must not be covered and is equipped with a thermal protection, location is indicated with a label on the upper side of the winter mat.



### APPLICATIONS

|               |   |
|---------------|---|
| Outdoor areas | ✓ |
| Indoor        |   |

### ACCESSORIES

|            |  |
|------------|--|
| Thermostat |  |
|------------|--|

### TECHNICAL DATA

|                          |                                    |
|--------------------------|------------------------------------|
| Supply voltage           | 230 V - 50 Hz                      |
| Nominal coverage effect  | 300 W/m <sup>2</sup>               |
| Supply cable             | 1,5 mm <sup>2</sup> H07RN-F • 2,5m |
| Construction             | PVC FR/polyester, orange           |
| Max. temperature         | 55 °C                              |
| Min. bending radius      | 50mm                               |
| Enclosure classification | IP 66                              |
| Warranty                 | 2 years                            |
| Approvals                | CE                                 |
| Standards                | EN 62395 • EN 60335-1              |

### LINK TO OUR WEBSITE



Version 2-102023

Heatcom Corporation A/S  
Barmstedt Allé 6  
DK-5500 Middelfart  
Tel. +45 63 41 77 77  
Sales@Heatcom.dk



## MOBILE WINTER MAT - SCHUKO

| DESCRIPTION                   | DIMENSION | EFFECT | CURRENT |
|-------------------------------|-----------|--------|---------|
| Mobile winter mat - 1 x 3 m   | 1 x 3 m   | 925 W  | 4,0 A   |
| Mobile winter mat - 0,8 x 6 m | 0,8 x 6 m | 1520 W | 6,6 A   |

## MOBILE WINTER MAT - IEC 309

| DESCRIPTION                   | DIMENSION | EFFECT | CURRENT |
|-------------------------------|-----------|--------|---------|
| Mobile winter mat - 1 x 3 m   | 1 x 3 m   | 925 W  | 4,0 A   |
| Mobile winter mat - 0,8 x 6 m | 0,8 x 6 m | 1520 W | 6,6 A   |

## MOBILE WINTER MAT - DK

| DESCRIPTION                   | DIMENSION | EFFECT | CURRENT |
|-------------------------------|-----------|--------|---------|
| Mobile winter mat - 1 x 3 m   | 1 x 3 m   | 925 W  | 4,0 A   |
| Mobile winter mat - 0,8 x 6 m | 0,8 x 6 m | 1520 W | 6,6 A   |

Version 2-102023

Heatcom Corporation A/S  
Barmstedt Allé 6  
DK-5500 Middelfart  
Tel. +45 63 41 77 77  
Sales@Heatcom.dk