



Microinverter Datasheet

HMT-1600-4T
HMT-1800-4T
HMT-2000-4T

Description

Hoymiles new generation microinverter HMT-2000 series is designed to accommodate the high-powered PV modules, with maximum output power up to 2000 VA and maximum DC input current up to 16 A.

The innovative 4-input design enables faster installation and lower cost, and makes HMT-2000 series a very cost-effective choice.

The new Sub-1G wireless solution enables more stable communication with Hoymiles gateway DTU. Smart platform S-Miles Cloud makes it possible to module-level monitoring and remote O&M.

Features

- | | | | |
|----|--|----|--|
| 01 | Three-phase output, more suitable for commercial and industrial applications | 04 | 4-in-1 design enables faster installation and comes with a lower cost |
| 02 | With output power up to 2000 VA, compatible with 182 mm/210 mm PV module | 05 | Safer for rooftop solar stations with rapid shutdown compliance and isolated transformer |
| 03 | Grid protection relay integrated | 06 | Sub-1G wireless solution allows stable communication in commercial and industrial settings |

Technical Specifications

Model	HMT-1600-4T	HMT-1800-4T	HMT-2000-4T
Input Data (DC)			
Commonly used module power (W)	320 to 540+	360 to 600+	400 to 670+
Maximum input voltage (V)	65		
MPPT voltage range (V)	16–60		
Minimum/Maximum start-up voltage(V)	22/60		
Maximum input current (A)	4 × 14	4 × 15	4 × 16
Maximum input short circuit current (A)	4 × 25		
Number of MPPTs	2		
Number of inputs per MPPT	2		
Output Data (AC)			
Grid Type	Three Phase		
Rated output power (VA)	1600	1800	2000
Rated output current (A)	2.32 × 3	2.61 × 3	2.9 × 3
Nominal output voltage (V)	230/400, 3W+N+PE		
Nominal frequency (Hz)	50		
Power factor (adjustable)	> 0.99 default		
Total harmonic distortion	< 3%		
Maximum units per 12 AWG branch ¹	8	7	6
Maximum units per 10 AWG branch ¹	13	12	11
Efficiency			
CEC peak efficiency	96.50%		
Nominal MPPT efficiency	99.80%		
Night power consumption (mW)	< 50		
Mechanical Data			
Ambient temperature range (°C)	-40 to +65		
Storage temperature range (°C)	-40 to +85		
Dimensions (W × H × D [mm])	326 × 222 × 40.6		
Weight (kg)	5.9		
Enclosure rating	Outdoor-IP67		
Cooling	Natural convection-No fans		
Features			
Communication	Sub-1G		
Type of isolation	Galvanically Isolated HF Transformer		
Monitoring	S-Miles Cloud ²		
Compliance	VDE-AR-N 4105: 2018, EN 50549-1:2019, VFR 2019, IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4, IEC/EN 61000-3-2/-3		

*1 Refer to local requirements for exact number of microinverters per branch.

*2 Hoymiles Monitoring System